



# PX210


## TANDEM DUAL WHEEL PINTLE HITCH

Job to job the PX210 does the heavy lifting so you don't have to.

25,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102", 28' x 102"  
30' x 102", 32' x 102", 35' x 102", 38' x 102", 40' x 102"

**DM** POWDER COAT  
COATING SYSTEM



### AVAILABLE WHEELS



SILVER (standard)



BLACK

### STANDARD FEATURES

**LOADING STYLE:** 12' Hydraulic Dovetail, Max Ramps, or Straight Deck

**AXLES:** 2 - 10,000 lb General Duty Electric Brake, Oil Bath

**CROSS-MEMBERS:** 3" Channel on 16" Centers w/Formed Gussets

**FRAME:** 16" Engineered Beam (Low Profile)

**JACK:** 2 - 12,000 lb Drop-Leg Jacks

**LACE RAIL:** 6" Channel

**STAKE POCKETS:** 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools

**STORAGE:** HD V-Tongue Lid w/Gas Shock Assist in Tongue

**SWAY CONTROL:** Standard on 30' - 40' models

**TIRES:** ST235/80R16 Radial, Dually

**TONGUE:** 16" Engineered Tongue w/60K Pintle Eye

### POPULAR UPGRADES

Electric-Over-Hydraulic Drum or Disc Brakes

3" Channel Cross-Members on 12" Centers w/Formed Gussets

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

14" x 14" x 36" Under-Slung Box

Sway Control Pipe (for 20' - 28' models)

ST215/75R17.5 Radial Dually Tires