



PX212


TANDEM DUAL WHEEL PINTLE HITCH

Born to work - Day in and Day out.

25,900 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102", 28' x 102"
30' x 102", 32' x 102", 35' x 102", 38' x 102", 40' x 102"

DM POWDER COAT
COATING SYSTEM



AVAILABLE WHEELS



SILVER (standard)



BLACK

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, or Straight Deck

AXLES: 2 - 12,000 lb General Duty Electric Brake, Oil Bath

CROSS-MEMBERS: 3" Channel on 16" Centers w/Formed Gussets

FRAME: 16" Engineered Beam (Low Profile)

JACK: 2 - 12,000 lb Drop-Leg Jacks

LACE RAIL: 6" Channel

STAKE POCKETS: 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools

STORAGE: HD V-Tongue Lid w/Gas Shock Assist in Tongue

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial, Dually

TONGUE: 16" Engineered Tongue w/60K Pintle Eye

POPULAR UPGRADES

Electric-Over-Hydraulic Disc Brakes

3" Channel Cross-Members on 12" Centers w/Formed Gussets

Blackwood Floor

2 - 25,000 lb Two Speed Drop-Leg Jacks

14" x 14" x 36" Under-Slung Box

Sway Control Pipe (for 20' - 28' models)

ST215/75R17.5 Radial Dually Tires