







FMAX207

SINGLE WHEEL TANDEM AXLE GOOSENECK

Sporting a class exclusive 14" Engineered Beam frame, the FMAX207 is in a league of its own.

15,500 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102" 28' x 102", 30' x 102", 32' x 102", 35' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 7,000 lb Super Lube , Self-Adjust Electric Brakes

COUPLER: Curt Coupler

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 14" Engineered Beam 2.0

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets

and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial



ONYX ARTIC SCARLET CEMENT CARBON PLATINUM SILVER MOCHA DYNAMIC BLUE METALLIC METALLIC

COMMERCIAL TRACTOR INDUSTRIAL LIME TACTICAL CUSTOM
YELLOW GREEN ORANGE GREEN TAN

AVAILABLE WHEELS





TWO TONE ALUMINUM

POPULAR UPGRADES

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Electric-Over-Hydraulic Disc Brakes

Bolt-on LED Flood Lights, 2700 Lumens (Pair)

2 - 10,000 lb Hydraulic Jacks

7'x 8' Weld-On/Bolt-On Deck on the Neck

14" x 14" x 42" Under-Slung Box

ST215/75R17.5 Radial Tires