



FMAX208

SINGLE WHEEL TANDEM AXLE GOOSENECK

When power to weight is key the FMAX208 delivers in a lights out fashion.

18,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102", 28' x 102"
30' x 102", 32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 8,000 lb Oil Bath Electric Brakes

COUPLER: 25,000 lb Bulldog BX1

CROSS-MEMBERS: 3" Channel on 16" Centers w/Formed Gussets

FRAME: 16" Engineered Beam (Low Profile)

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools

STORAGE: Diamond Plate Neck Box w/ Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST215/75R17.5 Radial

DM POWDER COAT
COATING SYSTEM

STANDARD COLORS								
	BLACK	WHITE	RED	CEMENT GRAY	METALLIC GRAY	METALLIC SILVER	METALLIC MOCHA	METALLIC BLUE
SPECIAL COLORS								
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	CUSTOM COLOR			

AVAILABLE WHEELS



SILVER (standard)



BLACK

POPULAR UPGRADES

- 3" Channel Cross-Members on 12" Centers w/Formed Gussets
- Electric-Over-Hydraulic Disk Brakes
- Blackwood Floor
- 2 - 10,000 lb Hydraulic Jacks
- 7'x 8' Weld-On/Bolt-On Deck on the Neck
- 14" x 14" x 36" Under-Slung Box