



FMAX210SS

TANDEM SUPER SINGLE GOOSENECK

The FMAX210 Super Single does the kind of work other Single Wheel goosenecks only dream of.

25,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102", 28' x 102"
30' x 102", 32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 10,000 lb General Duty Electric Brake, Oil Bath

COUPLER: 25,000 lb Bulldog BX1

CROSS-MEMBERS: 3" Channel on 16" Centers w/Formed Gussets

FRAME: 16" Engineered Beam (*Low Profile*)

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools

STORAGE: Diamond Plate Neck Box w/ Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/75R17.5 18 Ply Radial, Super Single

DM POWDER COAT
COATING SYSTEM

STANDARD COLORS									
	BLACK	WHITE	RED	CEMENT GRAY	METALLIC GRAY	METALLIC SILVER	METALLIC MOCHA	METALLIC BLUE	
SPECIAL COLORS									
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	CUSTOM COLOR				

AVAILABLE WHEELS



SILVER (standard)



BLACK

POPULAR UPGRADES

- Electric-Over-Hydraulic Drum or Disc Brakes
- 3" Channel Cross-Members on 12" Centers w/Formed Gussets
- Blackwood Floor
- 2 - 10,000 lb Hydraulic Jacks
- 7'x 8' Weld-On/Bolt-On Deck on the Neck
- 14" x 14" x 36" Under-Slung Box