



PX312

TRIPLE DUAL WHEEL PINTLE HITCH

Work begins when the PX312 shows up and shows out.

30,000 lb GVWR

Available Sizes: 25' x 102", 28' x 102", 30' x 102"
32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 3 - 12,000 lb General Duty Electric Brake, Oil Bath

CROSS-MEMBERS: 3" Channel on 16" Centers w/Formed Gussets

FRAME: 16" Engineered Beam 20' - 32' (Low Profile)
18" Engineered Beam 35' - 40' (Low Profile)

JACK: 2 - 12,000 lb Drop-Leg Jacks

LACE RAIL: 6" Channel

STAKE POCKETS: 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools

STORAGE: HD V-Tongue Lid w/Gas Shock Assist in Tongue

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial, Dually

TONGUE: 16" Engineered Tongue w/60K Pintle Eye



POWDER COAT

STANDARD COLORS



SPECIAL COLORS



AVAILABLE WHEELS



SILVER (standard)



BLACK

POPULAR UPGRADES

40,000 lb GVWR Package

Electric-Over-Hydraulic Disc Brakes

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

14" x 14" x 36" Under-Slung Box

Air Ride Suspension

ST215/75R17.5 Radial Dually Tires