









903.572.2834 | www.diamondc.com



FMAX208

SINGLE WHEEL TANDEM AXLE GOOSENECK

When power to weight is key the FMAX208 delivers in a lights out fashion.

18,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102", 28' x 102" 30' x 102", 32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 8,000 lb Oil Bath Electric Brakes

COUPLER: 25,000 lb Bulldog BX1

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam (Low Profile)

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets

and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST215/75R17.5 Radial



POWDER COAT























GREEN

TAN

AVAILABLE WHEELS



POPULAR UPGRADES

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Electric-Over-Hydraulic Disk Brakes

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

7'x 8' Weld-On/Bolt-On Deck on the Neck

14" x 14" x 36" Under-Slung Box