



FMAX216

TANDEM DUAL WHEEL GOOSENECK

30,000 - 40,000 GVWR and up to 1,800 pounds lighter curb weight than the competition. Need we say more? #doWORK

30,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102"
28' x 102", 30' x 102", 32' x 102", 35' x 102", 38' x 102"
40' x 102", 44' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 16,000 lb General Duty Electric Brake, Oil Bath

COUPLER: 30,000 lb Bulldog BX1

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 20' - 32' (Low Profile)
18" Engineered Beam 35' - 44' (Low Profile)

JACK: 2 - 12,000 lb Drop-Leg Jacks


NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 44' models

TIRES: ST215/75R17.5 Radial, Dually



AVAILABLE WHEELS



BLACK

POPULAR UPGRADES

40,000 lb GVWR Package

Electric-Over-Hydraulic Drum Brakes

Blackwood Floor

2 - 25,000 lb Two Speed Drop-Leg Jacks

7'x 8' Weld-On/Bolt-On Deck on the Neck

14" x 14" x 36" Under-Slung Box

Air Ride Suspension 