



FMAX307

SINGLE WHEEL TRIPLE AXLE GOOSENECK

Whether it's hauling tractors, equipment, hay, or toys - the FMAX307 will deliver 24/7/365.

24,000 lb GVWR

Available Sizes: 125' x 102", 28' x 102", 30' x 102"
32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 3 - 7,000 lb Super Lube , Self-Adjust Electric Brakes

COUPLER: 25,000 lb Bulldog BX1

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam (*Low Profile*)

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial

DM POWDER COAT
COATING SYSTEM

STANDARD COLORS								
	BLACK	WHITE	RED	CEMENT GRAY	METALLIC GRAY	METALLIC SILVER	METALLIC MOCHA	METALLIC BLUE
SPECIAL COLORS								
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	DESERT TAN	CUSTOM COLOR		

AVAILABLE WHEELS

BLACK	TWO TONE ALUMINUM

POPULAR UPGRADES

- 3" I-Beam Cross-Members on 12" Centers with Formed Gussets
- Electric-Over-Hydraulic Disk Brakes
- Blackwood Floor
- 2 - 10,000 lb Hydraulic Jacks
- 7'x 8' Weld-On/Bolt-On Deck on the Neck
- 14" x 14" x 36" Under-Slung Box
- ST215/75R17.5 Radial Tires