



LPX

LOW PROFILE EXTREME DUTY EQUIPMENT TRAILER

This Low Profile equipment trailer has attitude, style and strength. The 8" I-Beam frame is the backbone of this animal.

14,000 - 24,000 lb GVWR

Available Sizes: 16' x 82", 18' x 82", 20' x 82"

22' x 82", 24' x 82", 26' x 82", 28' x 82", 30' x 82"

STANDARD FEATURES

AXLES: 2 - 7,000 lb Drop Super Lube, Self-Adjust Electric Brakes

BRAKES: Electric Drum

COUPLER: 2-5/16" - 15,000 lb Adjustable Cast

CROSS-MEMBERS: 3" I-Beam on 16" Centers

FENDERS: 14 ga Teardrop, Diamond Plate, Bolt-On

FLOOR: 2" Treated Lumber

FRAME: 8"x10lb I-Beam Tongue/Frame Design

JACK: 12,000 lb Drop-Leg Jack

RAMPS: 60" Rear Slide-In (3" Channel)

TIRES: ST235/80R16 Radial

TONGUE: 8"x10lb I-Beam Tongue/Frame Design



POWDER COAT

STANDARD
COLORS



BLACK



WHITE



RED



CEMENT
GRAY



METALLIC
GRAY



METALLIC
SILVER



METALLIC
MOCHA



METALLIC
BLUE

SPECIAL
COLORS



COMMERCIAL
YELLOW



TRACTOR
GREEN



INDUSTRIAL
ORANGE



LIME
GREEN



DESERT
TAN



CUSTOM
COLOR

AVAILABLE WHEELS



BLACK



TWO TONE ALUMINUM

POPULAR UPGRADES

24,000 lb / 18,000 lb / 20,000 lb GVWR Package

24" Diamond Plate Dove with Cleats

3/16" Diamond Plate Fenders, Super Heavy Duty

Max Ramps

Engineered Beam Technology standard on all 22" + models with GVWR upgrade

Gooseneck Package