



PX310

TRIPLE DUAL WHEEL PINTLE HITCH

Heavy duty doesn't have to mean heavy weight. Lighter weight, stronger frame - PX310 delivers more.

30,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102", 28' x 102"
30' x 102", 32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 3 - 10,000 lb General Duty Electric Brake, Oil Bath

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 20' - 32' (Low Profile)
18" Engineered Beam 35' - 40' (Low Profile)

JACK: 2 - 12,000 lb Drop-Leg Jacks

LACE RAIL: 6" Channel

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: HD V-Tongue Lid with Gas Shock Assist in Tongue

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial, Dually

TONGUE: 16" Engineered Tongue with 60K Pintle Eye

DM COATING SYSTEM POWDER COAT

STANDARD COLORS								
	BLACK	WHITE	RED	CEMENT GRAY	METALLIC GRAY	METALLIC SILVER	METALLIC MOCHA	METALLIC BLUE
SPECIAL COLORS								
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	DESERT TAN	CUSTOM COLOR		

AVAILABLE WHEELS



BLACK

POPULAR UPGRADES

Electric-Over-Hydraulic Drum or Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

14" x 14" x 36" Under-Slung Box

ST215/75R17.5 Radial Dually Tires