

SDX216

TANDEM DUAL WHEEL STEP DECK

With up to a 40,000 GVWR, 53' long, and an 18" monster Engineered Beam frame, the SDX216 means business. #doWORK

30,000-40,000 lb GVWR

Available Sizes: 48' x 102", 50' x 102 , 53' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 16,000 lb Heavy-Duty Electric Brake, Oil Bath

COUPLER: 30,000 lb Square Adjustable

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 18" Engineered Beam (Low Profile)

JACK: 2 - 25,000 lb Two Speed Drop-Leg Jacks

NECK: 10' Step Deck with Slide-In Ramps

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: 14"x14"x42" Under-Slung Box

SWAY CONTROL: Sway Control Pipe Standard

TIRES: ST215/75R17.5 Radial, Dually



AVAILABLE WHEELS



POPULAR UPGRADES

40,000 lb GVWR Package Electric-Over-Hydraulic Drum Brakes

Blackwood Floor

King-Pin Adapter

Warrior Winch Package

102" Underslung Dunnage Rack

Air Ride Suspension @ SUSPENSIONS