



FMAX207

SINGLE WHEEL TANDEM AXLE GOOSENECK

Sporting a class exclusive 14" Engineered Beam frame, the FMAX207 is in a league of its own.

15,500 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102"

28' x 102", 30' x 102", 32' x 102", 35' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 7,000 lb Super Lube , Self-Adjust Electric Brakes

COUPLER: 25,000 lb Bulldog BX1

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 14" Engineered Beam 2.0

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck


STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial

DM POWDER COAT



AVAILABLE WHEELS



BLACK



TWO TONE ALUMINUM

POPULAR UPGRADES

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Electric-Over-Hydraulic Disk Brakes

Bolt-on LED Flood Lights, 2700 Lumens (Pair)

2 - 10,000 lb Hydraulic Jacks

7'x 8' Weld-On/Bolt-On Deck on the Neck

14" x 14" x 36" Under-Slung Box

ST215/75R17.5 Radial Tires