



# FMAX210SS

## TANDEM SUPER SINGLE GOOSENECK

The FMAX210 Super Single does the kind of work other Single Wheel goosenecks only dream of.

25,000 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102"

28' x 102", 30' x 102", 32' x 102", 35' x 102"

38' x 102", 40' x 102"

### STANDARD FEATURES

**LOADING STYLE:** 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

**AXLES:** 2 - 10,000 lb General Duty Electric Brake, Oil Bath

**COUPLER:** 25,000 lb Bulldog BX1

**CROSS-MEMBERS:** 3" I-Beam on 16" Centers with Formed Gussets

**FRAME:** 16" Engineered Beam (*Low Profile*)

**JACK:** 2 - 12,000 lb Drop-Leg Jacks

**NECK:** 12" Engineered Neck

**STAKE POCKETS:** 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

**STORAGE:** Diamond Plate Neck Box with Gas Shock-Assisted Lid

**SWAY CONTROL:** Standard on 30' - 40' models

**TIRES:** ST235/75R17.5 18 Ply Radial, Super Single

### DM POWDER COAT



### AVAILABLE WHEELS



BLACK

### POPULAR UPGRADES

Electric-Over-Hydraulic Drum or Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

7'x 8' Weld-On/Bolt-On Deck on the Neck

14" x 14" x 36" Under-Slung Box