



# FMAX212

## TANDEM DUAL WHEEL GOOSENECK

Tested and proven - The FMAX212 owns work.

25,900 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102"

28' x 102", 30' x 102", 32' x 102", 35' x 102"

38' x 102", 40' x 102", 44' x 102"

### STANDARD FEATURES

**LOADING STYLE:** 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

**AXLES:** 2 - 12,000 lb Heavy Duty, Oil Bath

**COUPLER:** 30,000 lb Bulldog BX1

**CROSS-MEMBERS:** 3" I-Beam on 16" Centers with Formed Gussets

**FRAME:** 16" Engineered Beam 2.0

**JACK:** 2 - 12,000 lb Drop-Leg Jacks

**NECK:** 12" Engineered Neck

**STAKE POCKETS:** 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

**STORAGE:** Diamond Plate Neck Box with Gas Shock Assisted Lid

**SWAY CONTROL:** Standard on 30' - 44' models

**TIRES:** ST235/80R16 Radial, Dually

### DM POWDER COAT

STANDARD COLORS								
	BLACK	WHITE	RED	CEMENT GRAY	METALLIC GRAY	METALLIC SILVER	METALLIC MOCHA	METALLIC DYNAMIC BLUE
SPECIAL COLORS								
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	DESERT TAN	CUSTOM COLOR		

### AVAILABLE WHEELS



BLACK

### POPULAR UPGRADES

Electric-Over-Hydraulic Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 25,000 lb Two Speed Drop-Leg Jacks

14" x 14" x 36" Under-Slung Box

Air Ride Suspension

ST215/75R17.5 Radial Dually Tires