









www.diamondc.com





# FMAX212SS

#### TANDEM SUPER SINGLE GOOSENECK

Inspired by the "Super Single" trend in the trucking industry, the FMAX212SS is pound for pound the strongest single wheel gooseneck on the planet.

### 25,900 lb GVWR

**Available Sizes:** 20' x 102", 22' x 102", 25' x 102" 28' x 102", 30' x 102", 32' x 102", 35' x 102", 38' x 102" 40' x 102", 44' x 102"

## STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 12,000 lb Heavy Duty, Oil Bath

COUPLER: 30,000 lb Bulldog BX1

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 2.0 JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets

and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 44' models TIRES: ST235/75R17.5 18 Ply Radial, Super Single



CEMENT







GREEN





GREEN

METALLIC



METALLIC



METALLIC

AVAILABLE WHEELS

ORANGE

METALLIC



BLACK

#### **POPULAR UPGRADES**

Electric-Over-Hydraulic Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

14" x 14" x 36" Under-Slung Box

Air Ride Suspension

