



# PX212

## TANDEM DUAL WHEEL PINTLE HITCH

Born to work - Day in and Day out.

25,900 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102",  
28' x 102", 30' x 102", 32' x 102", 35' x 102"  
38' x 102", 40' x 102"

### STANDARD FEATURES

**LOADING STYLE:** 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

**AXLES:** 2 - 12,000 lb Heavy Duty, Oil Bath

**CROSS-MEMBERS:** 3" I-Beam on 16" Centers with Formed Gussets

**FRAME:** 16" Engineered Beam 2.0

**JACK:** 2 - 12,000 lb Drop-Leg Jacks

**LACE RAIL:** 6" Channel

**STAKE POCKETS:** 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

**STORAGE:** HD V-Tongue Lid with Gas Shock Assist in Tongue

**SWAY CONTROL:** Standard on 30' - 40' models

**TIRES:** ST235/80R16 Radial, Dually

**TONGUE:** 16" Engineered Tongue with 60K Pintle Eye

### DM POWDER COAT

STANDARD COLORS								
	BLACK	WHITE	RED	CEMENT GRAY	METALLIC GRAY	METALLIC SILVER	METALLIC MOCHA	METALLIC DYNAMIC BLUE
SPECIAL COLORS								
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	DESERT TAN	CUSTOM COLOR		

### AVAILABLE WHEELS



BLACK

### POPULAR UPGRADES

Electric-Over-Hydraulic Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 25,000 lb Two Speed Drop-Leg Jacks

14" x 14" x 36" Under-Slung Box

ST215/75R17.5 Radial Dually Tires