

ENGINEERED BEAM

TECHNOLOGY



www.diamondc.com



PX310

TRIPLE DUAL WHEEL PINTLE HITCH

Heavy duty doesn't have to mean heavy weight. Lighter weight, stronger frame - PX310 delivers more.

30,000 lb GVWR

Available Sizes: 25' x 102", 28' x 102", 30' x 102" 32' x 102", 35' x 102", 38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 3 - 10,000 lb General Duty Electric Brake, Oil Bath

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 2.0 20' - 32' 18" Engineered Beam 2.0 35' - 40'

JACK: 2 - 12,000 lb Drop-Leg Jacks

LACE RAIL: 6" Channel

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: HD V-Tongue Lid with Gas Shock Assist in Tongue

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial, Dually

TONGUE: 16" Engineered Tongue with 60K Pintle Eye



AVAILABLE WHEELS



POPULAR UPGRADES

Electric-Over-Hydraulic Drum or Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 10,000 lb Hydraulic Jacks

14" x 14" x 36" Under-Slung Box

ST215/75R17.5 Radial Dually Tires