

REVIEW CONFIGURATION

Part Name	Type
Model - FMAX212	
Package Options - Standard	option
Loading Style - 12' Hydraulic Dovetail	option
Length/Width - 30' x 102" HDT	
GVWR - 25,900 lb	standard
Dove - 12' Fully Automatic Hydraulic Dovetail	standard
Axles - 2 - 12,000 lb Heavy Duty, Oil Bath	standard
Brakes - Electric-Over-Hydraulic Disc Brakes	option
Suspension - Hutch Heavy Duty Adjustable Suspension	option
Pull Type - 12" Engineered Gooseneck	standard
Frame - 16" Engineered Beam 2.0	standard
Jack - 2 - 20,000 lb Hydraulic Jacks w/ Hydraulic Dovetail	option
Paint Type - DM Difference Maker Coating System	standard
Paint Color - Black	standard
Floor - 2" Treated Lumber	standard
Cross-Members - 3" I-Beam on 16" Centers w/ Formed Gussets	standard
Coupler - 2 - 5/16" Ball - 30,000 lb RAM Coupler	standard
Storage - Diamond Plate Neck Box w/ Gas Shock Assisted Lid	standard
Storage - Full Width Locking Chain Rack, Weld-on	add-on
Deck on the Neck - None	standard
Winch - Winch Tray	standard
Battery/Charger - Group 27 Series Battery w/110V 5amp Charger	standard
Battery/Charger - Solar Charging System, 7 watt	add-on
Lace Rail - 6" Channel Lace Rail	standard
Lights - All LED Lights	standard
Stake Pockets - 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools	standard
Slide Track & Ratchets - No Slide Track	standard
Steps - Front Retractable & Mid-Turn	standard
Sway Control - Standard on 30 - 44' model	standard
Wiring - Sealed Wiring Harness	standard
Tire Size - 215/75R17.5 16 Ply Radial, Dually	option
Wheel Color - Black	standard
Spare Mount - Under-Frame Spare Mount	standard
Spare Tire - Add Matching Spare Tire	add-on



CUSTOMER INFORMATION

Name: VBELT AND SON

REVIEW CONFIGURATION

Part Name	Type
Model - FMAX216	
Loading Style - 12' Hydraulic Dovetail	option
Length/Width - 30' x 102" HDT	
GVWR - 40,000 lb GVWR Package	option
Dove - 12' Fully Automatic Hydraulic Dovetail	standard
Axles - 2 - 16,000 lb Heavy Duty, Oil Bath	standard
Brakes - Electric-Over-Hydraulic Disc Brakes	standard
Suspension - Hutch Heavy Duty Adjustable Suspension	standard
Pull Type - 12" Engineered Gooseneck	standard
Frame - 16" Engineered Beam (Low Profile)	standard
Jack - 2 - 12,000 lb Hydraulic Jacks w/ Hydraulic Dovetail	option
Paint Type - DM Difference Maker Coating System	standard
Paint Color - Black	standard
Floor - 2" Oak Floor	option
Cross-Members - 3" I-Beam on 16" Centers w/ Formed Gussets	standard
Coupler - 3" Ball 40,000 lb Adjustable Telescoper	standard
Storage - Diamond Plate Neck Box w/ Gas Shock Assisted Lid	standard
Storage - Full Width Locking Chain Rack, Weld-on	add-on
Deck on the Neck - None	standard
Winch - Winch Mounting Plate w/ Receiver Tube	option
Battery/Charger - Group 27 Series Battery w/110V 5amp Charger	standard
Lace Rail - 6" Channel Lace Rail	standard
Stake Pockets - 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools	standard
Slide Track & Ratchets - No Slide Track	standard
Steps - Front Retractable & Mid-Turn	standard
Lights - All LED Lights	standard
Sway Control - Standard on 30 - 44' model	standard
Wiring - Sealed Wiring Harness	standard
Tire Size - 215/75R17.5 16 Ply Radial, Dually	standard
Wheel Color - Aluminum Outer Wheels	option
Spare Mount - Spare Mount in Gooseneck	standard
Spare Tire - Add Matching Spare Tire	add-on