



REVIEW CONFIGURATION

Part Name	QTY	Price Descriptor	Price	Type
Model - FMAX212				
Package Options - Standard				option
Loading Style - Straight Deck				option
Length/Width - 38' x 102" SD				
GVWR - 25,900 lb				standard
Ramps - 96" Rear Slide-In Ramps (3" Channel)				standard
Axles - 2 - 12,000 lb Heavy Duty, Oil Bath				standard
Brakes - Electric-Over-Hydraulic Disc Brakes				option
Suspension - Hutch Heavy Duty Adjustable Suspension				option
Pull Type - 12" Engineered Gooseneck				standard
Frame - 16" Engineered Beam 2.0				standard
Jack - 2 - 25,000 lb Two Speed Drop-Leg Jacks				option
Paint Type - DM Difference Maker Coating System				standard
Paint Color - Black				standard
Floor - 2" Treated Lumber				standard
Cross-Members - 3" I-Beam on 16" Centers w/ Formed Gussets				standard
Coupler - Shocker Hitch Air Ride Coupler				option
Storage - Diamond Plate Neck Box w/ Gas Shock Assisted Lid				standard
Storage - 14" x 14" x 42" Underslung Box				add-on
Deck on the Neck - None				standard
Winch - Winch Tray				standard
Battery/Charger - Solar Charging System, 7 watt				add-on
Lace Rail - 6" Channel Lace Rail				standard
Lights - All LED Lights				standard
Lights - Extra 3/4" Clearance Lights	10			add-on
Stake Pockets - 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools				standard
Slide Track & Ratchets - Full Length Slide Track (passenger side)				option
Slide Track & Ratchets - 4" Ratchets (Slide)	10			add-on
Steps - Front Retractable & Mid-Turn				standard
Sway Control - Standard on 30 - 44' model				standard
Wiring - Sealed Wiring Harness				standard
Tire Size - 235/80R16 14 Ply Radial, Dually				standard
Wheel Color - Black				standard
Spare Mount - Under-Frame Spare Mount				standard
Spare Tire - Add Matching Spare Tire				add-on