

## REVIEW CONFIGURATION

Part Name	QTY	Price Descriptor	Price	Туре
Model - FMAX216				
Package Options - Standard				option
Loading Style - Max Ramps				option
Length/Width - 44' x 102" MR				
<b>GVWR</b> - 30,000 lb				standard
<b>Dove</b> - 60" Dovetail with 2" x 2" x 1/8" Angle Cleats (Max Ramps)				standard
<b>Axles</b> - 2 - 16,000 lb Heavy Duty, Oil Bath				standard
Brakes - Electric-Over-Hydraulic Disc Brakes				standard
Suspension - Air Ride Suspension with Front Lift Axle				option
Spread Axle - Add Spread Axle				add-on
Spread Axle - 72" Spread Axle (Air Ride Only)				option
Pull Type - 12" Engineered Gooseneck				standard
Frame - 18" Engineered Beam 2.0				standard
Jack - 2 - 25,000 lb Two Speed Drop-Leg Jacks				option
Paint Type - DM Difference Maker Coating System				standard
Paint Color - Dynamic Blue Metallic				option
Floor - Blackwood Lumber Full				option
Cross-Members - 3" I-Beam on 12" Centers w/ Formed Gussets				option
Coupler - Shocker Hitch Air Ride Coupler				option
Storage - Diamond Plate Neck Box w/ Gas Shock Assisted Lid				standard
Storage - 16" Locking Chain Rack, Bolt-on				add-on
<b>Storage</b> - 14" x 14" x 42" Underslung Box	2			add-on
Storage - 102" Underslung Dunnage Rack				add-on
Deck on the Neck - None				standard
<b>Winch</b> - Winch Tray				standard
Battery/Charger - Trojan SCS 200 Battery Upgrade	2			option
Battery/Charger - Solar Charging System, 7 watt				add-on
Lace Rail - 6" Channel Lace Rail				standard
Stake Pockets - 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools				standard
Slide Track & Ratchets - Full Length Slide Track (driver side)				option
Slide Track & Ratchets - 4" Ratchets (Slide)	10			add-on
Steps - Front Retractable & Mid-Turn				standard
<b>Lights</b> - All LED Lights				standard
<b>Lights</b> - Flashing Caution LED Light on Rear				add-on
<b>Lights</b> - Bolt-on LED Loading Lights, 2000 Lumen				add-on
<b>Lights</b> - Extra 3/4" Clearance Lights	10			add-on
Sway Control - Standard on 30 - 44' model				standard
<b>Wiring</b> - Sealed Wiring Harness				standard
<b>Tire Size</b> - 215/75R17.5 16 Ply Radial, Dually				standard
Wheel Color - Aluminum Outer Wheels				option
Spare Mount - Under-Frame Spare Mount				standard
Spare Tire - Add Matching Spare Tire				add-on