



## REVIEW CONFIGURATION

Part Name	QTY	Price Descriptor	Price	Type
<b>Model</b> - FMAX210SS				
<b>Loading Style</b> - Max Ramps				option
<b>Length/Width</b> - 32' x 102" MR				
<b>GVWR</b> - 25,000 lb				standard
<b>Dove</b> - 60" Dovetail with 2" x 2" x 1/8" Angle Cleats (Max Ramps)				standard
<b>Axles</b> - 2 - 10,000 lb General Duty, Oil Bath				standard
<b>Brakes</b> - Electric Drum				standard
<b>Suspension</b> - Hutch Heavy Duty Adjustable Suspension				option
<b>Pull Type</b> - 12" Engineered Gooseneck				standard
<b>Frame</b> - 16" Engineered Beam 2.0				standard
<b>Jack</b> - 2 - 12,000 lb Drop-Leg Jacks				standard
<b>Paint Type</b> - DM Difference Maker Coating System				standard
<b>Paint Color</b> - Metallic Gray				option
<b>Floor</b> - 2" Treated Lumber				standard
<b>Cross-Members</b> - 3" I-Beam on 16" Centers w/ Formed Gussets				standard
<b>Coupler</b> - 2-5/16" Ball - 25,000 lb RAM Coupler				standard
<b>Storage</b> - Diamond Plate Neck Box w/ Gas Shock Assisted Lid				standard
<b>Storage</b> - 14" x 14" x 42" Underslung Box				add-on
<b>Deck on the Neck</b> - None				standard
<b>Winch</b> - Winch Tray				standard
<b>Lace Rail</b> - 6" Channel Lace Rail				standard
<b>Stake Pockets</b> - 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools				standard
<b>Slide Track &amp; Ratchets</b> - Full Length Slide Track (passenger side)				option
<b>Slide Track &amp; Ratchets</b> - 4" Ratchets (Slide)	8			add-on
<b>Steps</b> - Front Retractable & Mid-Turn				standard
<b>Lights</b> - All LED Lights				standard
<b>Sway Control</b> - Standard on 30 - 40' models				standard
<b>Wiring</b> - Sealed Wiring Harness				standard
<b>Tire Size</b> - 235/75R17.5 18 Ply Radial				option
<b>Wheel Color</b> - Black				standard
<b>Spare Mount</b> - Under-Frame Spare Mount				standard