



## REVIEW CONFIGURATION

Part Name	QTY	Price Descriptor	Price	Type
<b>Model</b> - FMAX212				
<b>Package Options</b> - Standard				option
<b>Loading Style</b> - Max Ramps				option
<b>Length/Width</b> - 28' x 102" MR				
<b>GVWR</b> - 25,900 lb				standard
<b>Dove</b> - 60" Dovetail with 2" x 2" x 1/8" Angle Cleats (Max Ramps)				standard
<b>Axles</b> - 2 - 12,000 lb Heavy Duty, Oil Bath				standard
<b>Brakes</b> - Electric-Over-Hydraulic Disc Brakes				option
<b>Suspension</b> - 6-Leaf Slipper Springs, 48" Spread				standard
<b>Pull Type</b> - 12" Engineered Gooseneck				standard
<b>Frame</b> - 16" Engineered Beam 2.0				standard
<b>Jack</b> - 2 - 12,000 lb Drop-Leg Jacks				standard
<b>Paint Type</b> - DM Difference Maker Coating System				standard
<b>Paint Color</b> - Red				option
<b>Floor</b> - 2" Treated Lumber				standard
<b>Cross-Members</b> - 3" I-Beam on 12" Centers w/ Formed Gussets				option
<b>Coupler</b> - 2 - 5/16" Ball - 30,000 lb RAM Coupler				standard
<b>Storage</b> - Diamond Plate Neck Box w/ Gas Shock Assisted Lid				standard
<b>Storage</b> - 14" x 14" x 42" Underslung Box				add-on
<b>Deck on the Neck</b> - Weld-on Deck on the Neck				option
<b>Winch</b> - Winch Tray				standard
<b>Lace Rail</b> - 6" Channel Lace Rail				standard
<b>Lights</b> - All LED Lights				standard
<b>Lights</b> - Bolt-on LED Loading Lights, 2000 Lumen				add-on
<b>Stake Pockets</b> - 2" x 3/8" Rub Rail w/ Stake Pockets & Pipe Spools				standard
<b>Slide Track &amp; Ratchets</b> - Full Length Slide Track (passenger side)				option
<b>Slide Track &amp; Ratchets</b> - 4" Ratchets (Slide)	6			add-on
<b>Steps</b> - Front Retractable & Mid-Turn				standard
<b>Wiring</b> - Sealed Wiring Harness				standard
<b>Tire Size</b> - 215/75R17.5 16 Ply Radial, Dually				option
<b>Wheel Color</b> - Black				standard
<b>Spare Mount</b> - Under-Frame Spare Mount				standard
<b>Spare Tire</b> - Add Matching Spare Tire				add-on