



FMAX212

TANDEM DUAL WHEEL GOOSENECK

Tested and proven - The FMAX212 owns work.

25,900 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102"

28' x 102", 30' x 102", 32' x 102", 35' x 102"

38' x 102", 40' x 102", 44' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 12,000 lb Heavy Duty, Oil Bath

COUPLER: 30,000 lb Ram Coupler

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 2.0

JACK: 2 - 12,000 lb Drop-Leg Jacks

NECK: 12" Engineered Neck

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: Diamond Plate Neck Box with Gas Shock Assisted Lid

SWAY CONTROL: Standard on 30' - 44' models

TIRES: ST235/80R16 Radial, Dually



POWDER COAT

STANDARD COLORS



BLACK



WHITE



RED



CEMENT GRAY



METALLIC GRAY



METALLIC SILVER



METALLIC DYNAMIC BLUE



COMMERCIAL YELLOW



TRACTOR GREEN



INDUSTRIAL ORANGE



LIME GREEN



DESERT TAN



CUSTOM COLOR

AVAILABLE WHEELS



BLACK

POPULAR UPGRADES

Electric-Over-Hydraulic Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Deck on the Neck

2 - 20,000 lb Hydraulic Jacks

14" x 14" x 36" Under-Slung Box

Air Ride Suspension

ST215/75R17.5 Radial Dually Tires