



PX212

TANDEM DUAL WHEEL PINTLE HITCH

Born to work - Day in and Day out.

25,900 lb GVWR

Available Sizes: 20' x 102", 22' x 102", 25' x 102",
28' x 102", 30' x 102", 32' x 102", 35' x 102"
38' x 102", 40' x 102"

STANDARD FEATURES

LOADING STYLE: 12' Hydraulic Dovetail, Max Ramps, XDR Ramps, or Straight Deck

AXLES: 2 - 12,000 lb Heavy Duty, Oil Bath

CROSS-MEMBERS: 3" I-Beam on 16" Centers with Formed Gussets

FRAME: 16" Engineered Beam 2.0

JACK: 2 - 12,000 lb Drop-Leg Jacks

LACE RAIL: 6" Channel

STAKE POCKETS: 2" x 3/8" Rub Rail with Stake Pockets and Pipe Spools

STORAGE: HD V-Tongue Lid with Gas Shock Assist in Tongue

SWAY CONTROL: Standard on 30' - 40' models

TIRES: ST235/80R16 Radial, Dually

TONGUE: 16" Engineered Tongue with 60K Pintle Eye

DM POWDER COAT

STANDARD COLORS								
	ONYX BLACK	ARTIC WHITE	SCARLET RED	CEMENT GRAY	CARBON METALLIC GRAY	PLATINUM SILVER METALLIC	MOCHA METALLIC	DYNAMIC BLUE METALLIC
SPECIAL COLORS								
	COMMERCIAL YELLOW	TRACTOR GREEN	INDUSTRIAL ORANGE	LIME GREEN	TACTICAL TAN	CUSTOM		

AVAILABLE WHEELS



BLACK

POPULAR UPGRADES

Electric-Over-Hydraulic Disc Brakes

3" I-Beam Cross-Members on 12" Centers with Formed Gussets

Blackwood Floor

2 - 25,000 lb Two Speed Drop-Leg Jacks

14" x 14" x 36" Under-Slung Box

ST215/75R17.5 Radial Dually Tires